

Disc scrubber driers

CT46

B50




Solution distribution from brush center avoids solution wastes.



Self-levelling mechanical system for an always perfect adherence between brush and floor.



Squeegee designed for the highest drying and productivity results.



Anti-foam system with special mechanical suction motor protection.



Deactivation and re-start of working function simply with a command on handle. It includes brush and suction delayed stop for irregular working stages.



Brush, blades and suction hoses replacement without tools.



Exclusive technologies

TCL on board battery charger (standard)



Topping-up Charger Limiter allows the best recharge management of batteries. It can double their life by keeping the maximum performance during the operating time.

Power Battery (optional)



Batteries with Dry Cell technology which don't require maintenance. Very low levels of auto-discharge and made from almost completely recyclable materials.

Chem Dose (optional)




Detergent dosing system separated from water supply. It allows consistent savings on chemical products. Tank easily removable.



Easy to use thanks to intuitive commands.



Adjusting handle even during working operations.



Yellow operator maintenance areas. Brush with maximum consumption indicator.



Tank easily removable to check the internal areas of machine.



Motor gear box, suction motor and electric components of high quality.

Main technical characteristics

Motors

- **Brush rotation:** independent oil bath motor gear box
- **Suction:** 3 stages with stainless steel fans and shaft

Plastics

- **Tanks:** great thickness high density polyethylene
- **Squeegee blades:** made in Latex usable on 4 sides
- **Hoses:** suction and discharge made in high resistance polyurethane
- **Wheels:** oil resistant

Other characteristics

- Nylon standard brush with maximum consumption indicator
- Solution adjust and closure valve
- Positioned in height discharge hose (ø 38 mm)
- Brush hook on machine side
- Automatic brush click-on/off

Mechanics

- **Front wheel:** transfer easily actionated from driving place (BT version)
- **Chassis:** double treatment with galvanizing + die-casting
- **Bearings:** shielded against humidity and water seepages
- **Bolts and nuts:** made in stainless steel where there are water contacts

Electric system

- **Carbon brushes:** easily changeable
- **Boards:** equipped with protective film against water and humidity
- **Solenoid valve:** with Viton membrane resistant against chemical agents
- **Display:** battery level

Control panel

Brush, solution and vacuum inserted by one unique command or singularly upon necessity.



Models

Code	Model	Scrubbing width (mm)	Squeegee width (mm)	Productivity (max speed) (m ² /h)	Brush no.	Solution tank (l)	Recovery tank (l)	Power supply	Max speed (Km/h)	Weight (Kg)	Dimensions (LxWxH) (mm)
3.126.037	CT46-B50	500	730	2475	1 (disc)	40	50	24 V (2x12 V) - 76 Ah	3.5	100*	821x576x1220

* charger included - batteries not include : (2x 3.217.005)

Accessories

Code	Standard
3.8006.SPPV01332	Nylon brush PPL - standard
3.8006.PMVR01534	Squeegee
3.8006.MPVR06287	Front squeegee blade (Latex)
3.8006.MPVR06288	Rear squeegee blade (Latex)
Code	Optional
3.8006.SPPV01335	Pad holder
3.8006.SPPV01413	Standard pad WHITE -19" (5 pieces)
3.8006.SPPV01431	Standard pad RED -19" (5 pieces)
3.8006.SPPV01449	Standard pad GREEN -19" (5 pieces)
3.8006.SPPV01467	Standard pad BLACK -19" (5 pieces)

CHEM-DOSE